



Ovens

ADVANCE PLUS ovens

GAS ADVANCE PLUS OVEN, APG-102

<u>DIMENSIONS</u>		Article	Packed
Length	mm	1.130,00	1.200,00
Depth	mm	1.063,00	1.200,00
Height	mm	1.117,00	1.270,00
Weigth	Kg	250,00	270,00
Volumen	m3	1,34	1,83
<u>ELECTRICITY</u>			
Electric power		KW	1,20
230V -1+N		2x1,5+T - 10 A	
230V - III			
400V - III+N			
<u>WATER</u>			
Water consumption (lit/h)			30,00
Pressure (Kg/cm2)			0,5 - 8
<u>GAS</u>			
Power		KW	35,00
		Kcal/h	30.100,00
LPG		Consumption (kg/h)	4,10
		Pressure (g/cm2)	37,00
Natural Gas		Consumption (m3/h)	5,50
		Pressure (g/cm2)	18,00
<u>STEAM</u>		Not used	
<u>AIR</u>		Not used	
<u>LEVEL SOUND</u>		(dB)	62,00
<u>Certificate EQNET- CE</u>			99BL580

GAS ADVANCE PLUS OVEN, APG-102

High quality, fast cooking :

- Professional quality and perfect results
- Easy to use and efficient

Capacity for 20 1/1-GN trays or 10 2/1-GN trays.

Stainless steel burner with electronic control system with sparking plug ignition.

Frequency modulation for the convection burner.

"Touch control" screen.

4 cooking methods: Steam, Adjustable Steam (Humidity control during cooking), Regeneration and Convection (up to 300°C).

Preheating option.

Fagor Easy cooking mode.

Fagor Cooking, range of cooking programmes.

Fagor Multi-Tray System, control cooking by tray.

Delayed programming for: Cooking, Low-temperature cooking and Washing.

Memory function: records the different cooking methods used.

3 Speeds - 2 power ranges.

Cold-Down chamber cooling system.

"Auto-reverse" system to reverse fan rotation.

5 wash programmes.

Multisensor temperature probe.

PC management software: History, recipes. HACCP, manuals...

HACCP cooking data recording system.

Steam generator equipped with limescale detector.

Steam generator automatically empties every 24 hours of cooking.

Semi-automatic limescale removal system.

Error detection system. "Repair service" mode system.

IPX-5 protection.

Retractable shower.

Electrical connection: 230 V - 1+N - 1,20 kW.

Gas heating power: 30,100 kcal/h - 35 kW.

Dimensions: 1,130 x 1,063 x 1,117 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	960	860	110		Prever Interruptor diferencial 30 mA
DRAIN	703	212	110	30x25	Pendiente del 5%
SOFT COLD WATER	989	625	110	3/4"	Prever llave de corte en la toma
COLD WATER	1.059	625	110	3/4"	Prever llave de corte en la toma
EXHAUST	774	239	1.120	120	
GAS	1.039	733	110	R.3/4"G	Prever regulador y llave de corte individual

