



## Ovens

### Regeneration ovens

## REGENERATION OVEN, HRH-102

### DIMENSIONS

|         |    | Article  | Packed   |
|---------|----|----------|----------|
| Length  | mm | 860,00   | 860,00   |
| Depth   | mm | 850,00   | 850,00   |
| Height  | mm | 1.115,00 | 1.115,00 |
| Weigth  | Kg | 102,00   | 105,00   |
| Volumen | m3 | 0,82     | 0,82     |

### ELECTRICITY

| Electric power | KW            |       |
|----------------|---------------|-------|
| 230V - 1+N     |               | 16,00 |
| 230V - III     |               |       |
| 400V - III+N   | 4x4+T - 32 A. |       |

### WATER

|                           |       |
|---------------------------|-------|
| Water consumption (lit/h) | 0,00  |
| Pressure (Kg/cm2)         | 2 - 4 |

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### REGENERATION OVEN, HRH-102

Regeneration oven with Temperature switch and Humidity control .  
 Tightness chamber with radiused corners .  
 Total thermic insulation with rock or glass wool, 35 mm thickness.  
 Long lasting front seals made up of food grade of high heat resistance.  
 Removable side racks to facilitate cleaning.  
 Internal drain for easy cleaning.  
 Ventilated heating provided by highefficiency protected heating elements.  
 Snap-shut door with internal glass.  
 Simplified, user-friendly controls.  
 Operating temperature 30°C - 160°C.  
 Regeneration or keeping warm mode.  
 Regeneration time setting knob, with warming light indicating operation.  
 Regeneration temperature setting switch 140°/160°C. It is advisable to set to 140°C for normal regenerating and 160°C for regenerating fried foods.  
 Humidity setting knob, with warming light indicating operation.  
 Chamber with safety thermostat.  
 Manual humidity vent.  
 Periodic reversal of direction of rotation of the fans for better air distribution.  
 Automatic stopping of fans when is opened.  
 End-of-cycle buzzer.  
 Adjustable feet.  
 Easy access to facilitate maintenance and repair.  
 Capacity: 10 GN-2/1 levels - 40 dishes.  
 Distance guides: 70 mm  
 Voltage: 400 V - 3+N  
 Power: 16 kW  
 Dimensions: 860 x 850 x 1.115 mm.

Support in option, not included.

| Connections points | X   | Y | Z  | Diameter | Information |
|--------------------|-----|---|----|----------|-------------|
| ELECTRICITY        | 714 | 0 | 70 |          |             |
| DRAIN              | 430 | 0 | 50 | 1/2      |             |
| SOFT COLD WATER    | 146 | 0 | 70 | 3/4      |             |

