



Ovens

Regeneration ovens

REGENERATION OVEN, HRT-081

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	800,00	800,00
Depth	mm	700,00	700,00
Height	mm	1.115,00	1.115,00
Weigth	Kg	90,00	93,00
Volumen	m3	0,62	0,63

ELECTRICITY

<u>Electric power</u>		KW	12,50
230V - 1+N			
230V - III			
400V - III+N		4x4+T - 25 A.	

WATER

Water consumption (lit/h)			0,00
Pressure (Kg/cm2)			

GAS

Not used

STEAM

Not used

AIR

Not used

REGENERATION OVEN, HRT-081

Regeneration oven with Temperature switch.
 Tightness chamber with radiused corners.
 Total thermic insulation with rock or glass wool, 35 mm thickness.
 Long lasting front seals made up of food grade of high heat resistance.
 Removable side racks to facilitate cleaning.
 Internal drain for easy cleaning.
 Ventilated heating provided by highefficiency protected heating elements.
 Snap-shut door with internal glass.
 Simplified, user-friendly controls.
 Operating temperature 30°C - 160°C.
 Regeneration temperature setting switch 140°/160°C. It is advisable to set to 140°C for normal regenerating and 160°C for regenerating fried foods.
 Chamber with safety thermostat.
 Manual humidity vent.
 Periodic reversal of direction of rotation of the fans for better air distribution.
 Automatic stopping of fans when is opened.
 End-of-cycle buzzer.
 Adjustable feet.
 Easy access to facilitate maintenance and repair.
 Capacity: 8 GN-1/1 levels - 16 dishes.
 Distance guides: 90 mm
 Voltage: 400 V - 3+N
 Power: 12,5 kW
 Dimensions: 800 x 700 x 1.115 mm.
 Support in option, not included.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	654	0	70		
DRAIN	400	0	50	1/2	

