



600 Series

Ranges 600

**ELECTRIC RANGE, CE6-20**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>400,00</b>	<b>425,00</b>
Depth	mm	<b>650,00</b>	<b>675,00</b>
Height	mm	<b>440,00</b>	<b>500,00</b>
Weigth	Kg	<b>25,00</b>	<b>28,00</b>
Volumen	m3	<b>0,11</b>	<b>0,16</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V -1+N		<b>4,00</b>
230V - III		<b>2x4+T - 32 A</b>
400V - III+N		<b>3x2,5+T - 25 A</b>
		<b>4x1,5+T - 16 A</b>

**WATER**

Not used

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

ELECTRIC RANGE, CE6-20

Made of stainless steel.

Cast iron hot- plates with shielded elements.

6 settings switch. Indicator lights.

Plates: 2 x 2000 W (Ø 220 mm).

Total power: 4 KW.

Dimensions: 400 x 650 x 440 mm.

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	321	335	0		Prever Interruptor diferencial

